



RESISTOR

8" | COMPOSITE SAFETY TOE
TB092663214




30-Day US and Canada only



COMPOSITE
SAFETY TOE



18KV ELECTRICAL
SHOCK



PUNCTURE
RESISTANT



ALL-WEATHER
TPU SOLE



INSULATED



ANTIMICROBIAL
ODOR CONTROL



FEATURES:

- Leather upper
- Composite safety toe
- Direct-inject construction
- Padded top collar
- Air-textured nylon tongue
- Insulated 200g Thermolite®
- Mesh lining with anti-microbial treatment
- Lightweight polyurethane midsole
- Cement construction
- Non-metallic shank
- Non-metallic plate
- Weight 9W 830g

ALL-WEATHER THERMOPLASTIC URETHANE OUTSOLE:

- Slip resistant
- Oil resistant per SATRA TM63
- Heat Resistant up to 248°F using EN/ISO 20344:2004 (120°C)
- Abrasion resistant
- Non Marking

DYNAMIC ANTI-FATIGUE TECHNOLOGY POLYURETHANE FOOTBED:

- Durable: resists compression set over time
- Resilient: recovers for next foot strike
- Mono-sided inverted Anti-Fatigue Technology cones
- Contoured bio-mechanically engineered top surface helps maintain proper gait
- Dynamic arch adapts to different foot shapes for maximum comfort
- Moisture-wicking open-cell top cover

7-11 12 13 14 15 W

USA Men's	7	7.5	8	8.5	9	9.5	10	10.5	11	12	13	14	15
USA Women's	8.5	9	9.5		10	10.5	11	11.5	12				
United Kingdom	6	6.5	7	7.5	8	8.5	9	9.5	10	11	12	13	14
Europe	39	40	41	41.5	42	42.5	43	43.5	44	46	47	48	49
Centimeters	25,0	26,0	26,0	26,5	27,0	27,5	28,0	28,5	29,0	30,0	31,0	32,0	33,0



RESISTOR

8" | COMPOSITE SAFETY TOE
TB092663214

- A. Composite Safety Toe
- B. Anti-Fatigue Technology PU Footbed
- C. Non-Metallic Shank
- D. Non-Metallic Puncture-Resistant Plate
- E. Lightweight, Cushioning PU Midsole
- F. All-Weather TPU Outsole

- ☑ A. Embout coqué en composite
- B. Semelle intérieure en PUR amortissante
- C. Tige non métallique
- D. Plaque résistante aux perforations non métallique
- E. Semelle Intercalaire en PUR légère et coussinée
- F. Semelle extérieure en TPUR toutes saisons

- ☑ A. Punta de seguridad compuesta
- B. Plantilla de PU con tecnología anti-fatigue
- C. Cambrellón no metálico
- D. Placa no metálica resistente a perforaciones
- E. Entresuela ligera, acolchonada de PU
- F. Suela de TPU para todos los climas



MEASUREMENTS:


(All measurements are external)

HIGHEST POINT ON COLLAR: 9 1/4" 234 mm

LOWEST POINT ON COLLAR: 8 1/8" 206 mm

LOWEST OPENING ON BOOT: 6 1/2" 165.1 mm

HEEL BREAST: 5/8"





RESISTOR

8" | COMPOSITE SAFETY TOE
TB092663214

SLIP TEST RATING



No shoe is "slip proof." Footwear is one small part of any Slip Hazard Assessment Defense Program. You should always consult with your Company Safety Manager to determine the most appropriate footwear for your work environment. Using this information, it is possible to seek advice from the Manufacturer or Distributor regarding appropriate application based on test results.

EXCERPT FROM CSA Z195-14 WHOLE SHOE SLIP RESULTS


TEST REPORT: FWT0208028A
OUTSOLE: PRO280 TEST LAB: 12A10

The below chart provides the slip scores for the outsole of the shoe

- HEEL / TALON / TALÓN
- FLAT / PLAT / PARTE PLANA
- MINIMUM REQUIRED / MINIMUM REQUIS / MÍNIMO REQUERIDO

Consult the slip resistance chart for the specific slip resistance rating for the outsole of the shoe.

CSA Z195-14





RESISTOR

8" | COMPOSITE SAFETY TOE
TB092663214



TECHNOLOGIES



Composite Safety Toe

Lightweight, non-metallic, asymmetrical-shaped toe cap. Meets US and Canadian safety standards including ASTM F2412-11 and ASTM F2413-11 I/75 and C/75 Impact and compression safety standards and CAN/CSA-Z195-14 Grade 1.



Electrical Shock Resistant

Meets CAN/CSA-Z195-14 safety standards for footwear incorporating electric shock-resistant soles.



Puncture Resistant

Flexible non-metallic plate minimizes the likelihood of puncture wounds. Meets US and Canadian safety standards including ASTM F2412-11, ASTM F2413-11 and ASTM F2892-11 PR puncture resistance and CAN/CSA-Z195-14 Grade 1 with protective soles.



All-Weather TPU Outsole

Specially-formulated thermoplastic urethane compound designed to maintain flexibility in variable weather conditions, providing enhanced traction on wet and frosted ice surfaces, plus slip, oil and abrasion resistance.



Antimicrobial Odor Control

Treatment to help prevent and control odors.



Anti-Fatigue Technology

A comfort system designed with shock-absorbing, geometrical technology that returns energy back to the foot to deliver all-day support and comfort.



30-Day Comfort Guarantee

If you don't believe Timberland PRO® footwear with Anti-Fatigue Technology, PowerFit™ comfort system or SensorFlex™ technology are not more comfortable than the brand you're currently wearing, return them within 30 days and we'll refund your purchase price, provided you still have your dated receipt of purchase. Call **1-888-802-9947** from US and **1-800-501-3054** from Canada. Available in the United States and Canada only.